




NEXTORCH

ENGLISH



G6R

Learn more on www.nextorch.com

SPECIFICATIONS

ANSI/PLATO-FL1	High	Low
☀️ Light Output	160 lm	18 lm
🕒 Run Time	5 h	50 h
📏 Beam Distance	155 m	50 m
🔨 Impact Resistance	1 m	
🌧️ Waterproof	IPX7, 1 m	

Weight and Dimensions Weight: 80 g / 2.82 oz (without battery)
Size: 127 mm (Length) × 34 mm (Head Diameter) × 28.8 mm (Body Diameter)

Body Material Nylon - fiber


Above tested specifications are strictly based on the standard of ANSI/PLATO-FL1. We tested G6R with 1×18650 (2600mAh) battery in 22°C±3°C. The specifications might be different when using a different battery or testing in a different environment.

FEATURES

- Ex ib II B T3 Gb Explosion proof grade, suitable for explosive gas atmospheres.
- Durable nylon-fiber body shell, water-proof and shock-resistant.
- Powered by 2600 mAh 18650 Li-ion battery with overcharge/discharge protection circuit.
- USB direct charge with LED indicator.

INSTRUCTIONS


Battery Installation



USB direct charge


To charge the G6R (with 18650 rechargeable battery) via a UC4 USB Port of a computer, wall charger or in-car charger, the indicator LED turns on when charging, it turns red to green when charging completed. (The charging port and the indicator LED are on the tailcap)

ON/OFF



* Charging time : About 4 hours.

Mode Switch



Wall-charger

Move the battery from the shell of flashlight, put the battery into the slot of the wall charger, the indicator LED turns on when charging, it turns red to green when charging completed. * Charging time : About 4 hours.

MAINTENANCE

1. Being infected with seawater or any corrosive chemicals, please rinse immediately with clean water.
2. Please use high quality batteries; Remove batteries when not working for a long time, and then store in a cool dry place.
3. If the waterproof O-ring is damaged, replace it immediately.

WARRANTY

1. NEXTORCH offers 5-year warranty.
2. NEXTORCH warrants our products to be free from any defects in workmanship and material, we will replace or return faulty item. NEXTORCH reserves the right to replace similar products if original one is discontinued.
3. The warranty excludes other accessories, but rechargeable batteries are warranted for 1 year from date of purchase.
4. Any accessories or products are not covered in the warranty, NEXTORCH can repair for users with reasonable fee.
5. Please scan the below QR code and access to NEXTORCH website (www.nextorch.com) to register your purchasing. Email us info@nextorch.com Call us: 0086-662-6602777 Or contact local dealer




CONTACT WITH NEXTORCH DESIGNER

In order to improve NEXTORCH, we appreciate you could offer our designers your after-use feedback and creative suggestions by scanning the following QR code. Thank you!



NEXTORCH

中文



G6R防爆手电

请登录: www.nextorch.com
获取更详尽的产品资讯。

性能参数

ANSI/PLATO-FL1	高亮	低亮
☀️ 亮度	160流明	18流明
🕒 续航时间	5小时	50小时
📏 照射距离	155米	50米
🔨 防跌高度	1米	
🌧️ 防水等级	IPX7, 水下1米	

规格 重量: 80克 (不含电池)
尺寸: 127毫米 (长) × 34毫米 (头径) × 28.8毫米 (筒径)

筒身材料 尼龙玻纤


上述参数严格按照ANSI/PLATO FL1 标准测试所得, 测试电池为1节18650 (2600mAh) 锂离子充电电池, 测试温度22°C±3°C, 测试电池或环境不同, 性能参数可能会有差异。

产品特点

- 本安型防爆手电, II B防爆等级, 可在除煤矿以外的所有爆炸性气体环境中使用。
- 高耐候性尼龙玻纤筒身, 强度高、耐腐蚀、抗老化。
- 采用带过充过放保护电路的18650可充电锂离子电池。
- USB直充设计, LED灯充电指示。

快速入门



电池安装



充电


直充
G6R防爆手电(使用18650锂离子电池)采用USB直充设计, 可通过专用的UC4充电线连接电脑、座充、车充等设备进行充电, 当指示灯从红色变为绿色, 充电完成。(充电孔及指示灯位于尾盖上)

打开/关闭



* G6R防爆手电充电时间: 约4小时

模式切换



外充
把电池从电筒里取出, 放进18650座充电电池仓内进行充电, 当座充指示灯从红色变为绿色, 充电完成。
* 充电时间: 约4个小时

保养注意事项

1. 当沾到海水或腐蚀物品时, 请及时用清水清洗;
2. 请使用优质电池, 并且在长时间不使用时, 请将电池取出, 放在阴凉处保存; 若产品采用不可拆卸的内置电池, 切勿自行更换电池, 以免导致产品无法正常运行或电池损坏。
3. 长时间使用后若发现O型圈磨损, 请及时更换。

售后/保修条款

1. 15天换货: NEXTORCH产品自售出日起15天内, 在正常使用的情况下, 若出现质量问题, 可免费更换同型号产品; 若该产品已停止生产, 则调换该型号升级品或不低于原产品性能的其他产品;
2. 5年免费保修期: NEXTORCH产品自售出日起5年内, 在正常使用的情况下, 若出现质量问题, 享受免费维修服务;
3. 充电电池类产品保修期为1年, 产品附加配件不在保修范围内;
4. 终身有限保修: 因不当使用引起的产品损坏或超出免费保修时间的产品, 我司将提供有偿保修, 费用以实际更换材料费用为准, 不另收人工费用;
5. 我司提供多种渠道进行维修服务, 您可通过扫描如下二维码在官网进行登记、发邮件至service@nextorch.com、致电400-8300-799或直接联系当地经销商进行售后服务;



与纳丽德设计师沟通

为更好地改进我们的产品, 您如果有产品改进反馈或创意提供给我们的设计师, 请扫描下方二维码, 联系我们的产品设计师。



成品尺寸: 80mm × 40mm
 展开尺寸: 280mm × 80mm
 检验标准: 尺寸±1mm
 印刷说明: 80克双胶纸双面印刷
 颜色: K
 虚线折痕