


NEXTORCH

ENGLISH



UT11

Learn more on  
www.nextorch.com

## SPECIFICATIONS

ANSI/PLATO-FL1	High (white)	Low (white)	Red and Blue Emergency Flash
Light Output	170 lm	20 lm	—
Run Time	2 h	11 h	81 h
Beam Distance	19 m	7 m	—
Impact Resistance	1 m		
Waterproof	IPX4		
Light Source	COB		
Battery	Built-in 640 mAh Lithium Battery		
Weight and Dimensions	Weight: 46.8 g Size: 60 mm(Length) × 46 mm(Width) × 17 mm(Height)		

Above tested specifications are strictly based on the standard of ANSI/PLATO-FL1. We tested UT11 with 640 mAh lithium battery in 22°C±3°C. The specifications might be different when using a different battery or testing in a different environment.


## QUICK START GUIDE

## Operating Instruction

- Long press 1 second to enter white light
- Tap to mode switching
- Long press 3 second to enter Red and Blue Emergency Flash

## Battery Indicator

- When the electric quantity higher than 70%, the indicator light is green
- Between 30% and 50%, the indicator light is orange
- Less than 30%, the indicator light is red

Battery  
indicator

## WARRANTY

- NEXTORCH warrants our products to be free from any defects in workmanship and/or materials for a period of 15-day from the date of purchase. We will replace it. NEXTORCH reserves the right to replace an obsolete product with a current production, like model.
- NEXTORCH warrants our products to be free of defect for 5-year of use. We will repair it.
- The warranty excludes other accessories, but rechargeable batteries are warranted for 1 year from the date of purchase.
- In the event that any issue with a NEXTORCH product is not covered under this warranty, NEXTORCH can arrange to have the product repaired for a reasonable fee.
- You could access to NEXTORCH website (www.nextorch.com) to gain warranty service information by scanning the following QR code. You could also:  
Email us at service@nextorch.com  
Call us: 0086-400-8300-799  
OR contact your local dealer/distributor.



## CONTACT WITH NEXTORCH DESIGNER

In order to improve NEXTORCH, we appreciate you could offer our designers your after-use feedback and creative suggestions by scanning the following QR code. Thank you!



NEXTORCH

中文



UT11

请登录: www.nextorch.com  
获取更多产品信息

## 性能参数

ANSI/PLATO-FL1	白光高亮	白光低亮	红蓝警闪
亮度	170 流明	20 流明	—
续航时间	2 小时	11 小时	81 小时
照射距离	19 米	7 米	—
防跌高度	1米		
防水等级	IPX4		
光源	COB		
电池	内置640mAh锂电池		
规格	重量: 46.8 克 尺寸 (灯头): 60 毫米(长) × 46 毫米(宽) × 17 毫米(高)		

上述参数严格按照ANSI/PLATO FL1 标准测试所得, 测试电池为640mAh锂电池, 测试温度 22°C±3°C, 测试电池或环境不同, 性能参数可能会有差异。

## 快速入门

## 操作

长按1秒开启白光, 短按切换白光低亮、高亮。  
长按3秒开启红蓝警闪模式, 长按1秒关闭。

## 电量指示

使用过程中, 电量高于70%时, 指示灯为绿色;  
电量为30%-70%时, 指示灯为橙色;  
电量低于30%时, 指示灯为红色。

电量  
指示灯

## 售后/保修条款

- 15天换货: NEXTORCH产品自售出之日起15天内, 在正常使用的情况下, 若出现质量问题, 可免费更换同型号产品; 若该产品已停止生产, 则调换该型号升级品或不低于原产品性能的其他产品;
- 5年免费保修期: NEXTORCH产品自售出之日起5年内, 在正常使用的情况下, 若出现质量问题, 享受免费维修服务;
- 充电电池类产品保修期为1年, 产品附加配件不在保修范围内;
- 终身有限保修: 因不当使用引起的产品损坏或超出免费保修时间的产品, 我司将提供有偿维修, 费用以实际更换材料费用为准, 不另收取人工费用;
- 我司提供多种渠道进行保修服务, 您可通过扫描如下二维码在官网进行登记、发邮件至service@nextorch.com、致电400-8300-799或直接联系当地经销商进行售后服务;



## 与纳丽德设计师沟通

为更好地改进我们的产品, 您如果有产品改进反馈或创意提供给我们的设计师, 请扫描下面的二维码, 联系我们的产品设计师。



成品尺寸: 80mm×40mm  
展开尺寸: 200mm×80mm  
检验标准: 尺寸±1mm  
印刷说明: 80克双胶纸双面印刷  
颜色: K  
虚线折痕